

EVINRUDE® E-TEC®

30 HP



SPECIFICATIONS

Engine Type	Inline 2-Cylinder E-TEC D.I.
Bore x Stroke - in (mm)	2.992 x 2.5 (76 x 64)
Displacement - cu in (cc)	35 (575)
Gear Ratio	2.15:1
Full Throttle RPM Range	5500-6000 RPM
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	56 Amps Total / 15 Amps Net Dedicated
Trim Range	-4° to 16°
Tilt Range	65°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - qt (L)	1.7 (1.6)
Recommended Oil	XPS Marine XD100 / XD50
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union

COLOR	SHAFT LENGTH - in. (mm)	STEERING	STARTING	TRIM METHOD	MODEL NO.	WEIGHT - lb (kg)	
Graphite	15 (381)	Tiller (Remote avail.)	Rope (Electric acc.)	Manual Tilt	E30DRG	150 (68)	
			Rope (Electric acc.)	Manual Tilt	E30DRGL	154 (70)	
	20 (508)	Tiller (Remote avail.)	Electric & Rope	Manual Tilt	E30GTEL	166 (75)	
			Electric & Rope	Power Trim & Tilt	E30DGTL	187 (85)	
			Remote (Tiller avail.)	Electric & Rope	Power Trim & Tilt	E30DPGL	181 (82)
White	15 (381)	Tiller (Remote avail.)	Rope (Electric acc.)	Manual Tilt	E30DRS	150 (68)	
			Rope (Electric acc.)	Manual Tilt	E30DRSL	154 (70)	
	20 (508)	Tiller (Remote avail.)	Electric & Rope	Power Trim & Tilt	E30DTSL	187 (85)	
			Remote (Tiller avail.)	Electric & Rope	Power Trim & Tilt	E30DPSL	181 (82)

* Variable Voltage Computer Controlled 56 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 15 Amp. Specifications subject to change.

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

EVINRUDE®